

DECLARATION OF PERFORMANCE

No. 13/2021

1. Unique identification code of the product-type:

Gränges_Konin_4016

2. Intended use or uses:

Intended for internal and external loaded construction elements of buildings

3. Manufacturer:

Gränges Konin S.A., Bolesława Prusa 2 Street, 00-493 Warsaw, Poland
Correspondence address: Hutnicza 1 Street, 62-510 Konin, Poland

4. System or systems of assessment and verification of constancy of performance:

System 2+

5. Harmonised standard:

EN 15088: 2005

Notified body/ies:

Research and Certification Department „ZETOM” prof. F. Stauba in Katowice sp. z o.o.,
Notified Body number 1436

6. Declared performance: Sheet, plate and strip aluminum alloy EN AW-4016 cold rolled

Essential characteristics	Performance	Harmonised technical specification																																																																																																				
Dimensional tolerances IDT EN 485-4	Thickness tolerances <table border="1" data-bbox="368 1149 1198 1742"> <thead> <tr> <th colspan="2" data-bbox="368 1149 644 1312" rowspan="2">Specified thickness [mm]</th> <th colspan="4" data-bbox="644 1149 1198 1182">Thickness tolerances [mm]</th> </tr> <tr> <th data-bbox="644 1182 783 1312">Up to and including 1000mm</th> <th data-bbox="783 1182 900 1312">Over 1000mm up to and including 1250mm</th> <th data-bbox="900 1182 1016 1312">Over 1250mm up to and including 1600mm</th> <th data-bbox="1016 1182 1198 1312">Over 1600mm up to and including 2000mm</th> </tr> <tr> <th data-bbox="368 1312 507 1361">Over</th> <th data-bbox="507 1312 644 1361">Up to and including</th> <th data-bbox="644 1312 783 1361">mm</th> <th data-bbox="783 1312 900 1361">mm</th> <th data-bbox="900 1312 1016 1361">mm</th> <th data-bbox="1016 1312 1198 1361">mm</th> </tr> </thead> <tbody> <tr><td>0,20</td><td>0,4</td><td>±0,02</td><td>±0,04</td><td>±0,05</td><td>-</td></tr> <tr><td>0,4</td><td>0,5</td><td>±0,03</td><td>±0,04</td><td>±0,05</td><td>±0,06</td></tr> <tr><td>0,5</td><td>0,6</td><td>±0,03</td><td>±0,05</td><td>±0,06</td><td>±0,07</td></tr> <tr><td>0,6</td><td>0,8</td><td>±0,03</td><td>±0,06</td><td>±0,07</td><td>±0,08</td></tr> <tr><td>0,8</td><td>1,0</td><td>±0,04</td><td>±0,06</td><td>±0,08</td><td>±0,09</td></tr> <tr><td>1,0</td><td>1,2</td><td>±0,04</td><td>±0,07</td><td>±0,09</td><td>±0,10</td></tr> <tr><td>1,2</td><td>1,5</td><td>±0,05</td><td>±0,09</td><td>±0,10</td><td>±0,11</td></tr> <tr><td>1,5</td><td>1,8</td><td>±0,06</td><td>±0,10</td><td>±0,11</td><td>±0,12</td></tr> <tr><td>1,8</td><td>2</td><td>±0,06</td><td>±0,11</td><td>±0,12</td><td>±0,14</td></tr> <tr><td>2</td><td>2,5</td><td>±0,07</td><td>±0,12</td><td>±0,13</td><td>±0,15</td></tr> <tr><td>2,5</td><td>3,0</td><td>±0,08</td><td>±0,13</td><td>±0,15</td><td>±0,17</td></tr> <tr><td>3,0</td><td>3,5</td><td>±0,10</td><td>±0,15</td><td>±0,17</td><td>±0,18</td></tr> <tr><td>3,5</td><td>4,0</td><td>±0,15</td><td>±0,20</td><td>±0,22</td><td>±0,23</td></tr> <tr><td>4,0</td><td>5,0</td><td>±0,18</td><td>±0,22</td><td>±0,24</td><td>±0,25</td></tr> </tbody> </table> <p data-bbox="368 1742 1198 1765">When measuring the thickness, a zone 10mm wide from the edges of the product shall be disregarded.</p>	Specified thickness [mm]		Thickness tolerances [mm]				Up to and including 1000mm	Over 1000mm up to and including 1250mm	Over 1250mm up to and including 1600mm	Over 1600mm up to and including 2000mm	Over	Up to and including	mm	mm	mm	mm	0,20	0,4	±0,02	±0,04	±0,05	-	0,4	0,5	±0,03	±0,04	±0,05	±0,06	0,5	0,6	±0,03	±0,05	±0,06	±0,07	0,6	0,8	±0,03	±0,06	±0,07	±0,08	0,8	1,0	±0,04	±0,06	±0,08	±0,09	1,0	1,2	±0,04	±0,07	±0,09	±0,10	1,2	1,5	±0,05	±0,09	±0,10	±0,11	1,5	1,8	±0,06	±0,10	±0,11	±0,12	1,8	2	±0,06	±0,11	±0,12	±0,14	2	2,5	±0,07	±0,12	±0,13	±0,15	2,5	3,0	±0,08	±0,13	±0,15	±0,17	3,0	3,5	±0,10	±0,15	±0,17	±0,18	3,5	4,0	±0,15	±0,20	±0,22	±0,23	4,0	5,0	±0,18	±0,22	±0,24	±0,25	EN 15088:2005
Specified thickness [mm]				Thickness tolerances [mm]																																																																																																		
		Up to and including 1000mm	Over 1000mm up to and including 1250mm	Over 1250mm up to and including 1600mm	Over 1600mm up to and including 2000mm																																																																																																	
Over	Up to and including	mm	mm	mm	mm																																																																																																	
0,20	0,4	±0,02	±0,04	±0,05	-																																																																																																	
0,4	0,5	±0,03	±0,04	±0,05	±0,06																																																																																																	
0,5	0,6	±0,03	±0,05	±0,06	±0,07																																																																																																	
0,6	0,8	±0,03	±0,06	±0,07	±0,08																																																																																																	
0,8	1,0	±0,04	±0,06	±0,08	±0,09																																																																																																	
1,0	1,2	±0,04	±0,07	±0,09	±0,10																																																																																																	
1,2	1,5	±0,05	±0,09	±0,10	±0,11																																																																																																	
1,5	1,8	±0,06	±0,10	±0,11	±0,12																																																																																																	
1,8	2	±0,06	±0,11	±0,12	±0,14																																																																																																	
2	2,5	±0,07	±0,12	±0,13	±0,15																																																																																																	
2,5	3,0	±0,08	±0,13	±0,15	±0,17																																																																																																	
3,0	3,5	±0,10	±0,15	±0,17	±0,18																																																																																																	
3,5	4,0	±0,15	±0,20	±0,22	±0,23																																																																																																	
4,0	5,0	±0,18	±0,22	±0,24	±0,25																																																																																																	

Essential characteristics	Performance							Harmonised technical specification			
Dimensional tolerances IDT EN 485-4	Width tolerances for sheet and plate							EN 15088:2005			
	Specified thickness [mm]		Width tolerance for specified width [mm]								
	Over	Up to and including	Up to and including 500mm	Over 500mm up to and including 1250mm	Over 1250mm up to and including 2000mm						
	0,20	3,0	+1,5 0	+3 0	+4 0						
3,0	6,0	+3 0	+4 0	+5 0							
6,0	20	+4 0	+5 0	+5 0							
Mechanical properties according to Internal documentation	Length tolerances for sheet and plate										
	Specified thickness [mm]		Length tolerance for specified length [mm]								
	Over	Up to and including	Up to and including 1000mm	Over 1000mm up to and including 2000mm	Over 2000mm up to and including 3000mm	Over 3000mm up to and including 4000mm	Over 5000mm	+0,2% of specified length			
	0,20	3,0	+3 0	+4 0	+6 0	+8 0					
	3,0	6,0	+4 0	+6 0	+8 0	+10 0					
	6,0	20	+6 0	+8 0	+10 0	+10 0					
	Width tolerances for strip										
	Specified thickness [mm]		Width tolerance for specified width [mm]								
	Over	Up to and including	Up to and including 100mm	Over 100mm up to and including 300mm	Over 300mm up to and including 500mm	Over 500mm up to and including 1250mm	Over 1250mm up to and including 1650mm				
	0,20	0,6	+0,3 0	+0,4 0	+0,6 0	+1,5 0	+2,5 0				
0,6	1,0	+0,3 0	+0,5 0	+1 0	+1,5 0	+2,5 0					
1,0	2,0	+0,4 0	+0,7 0	+1,2 0	+2 0	+2,5 0					
2,0	3,0	+1 0	+1 0	+1,5 0	+2 0	+2,5 0					
3,0	5,0	-	+1,5 0	+2 0	+3 0	+3 0					

Essential characteristics	Performance	Harmonised technical specification
Weldability IDT EN 1999-1-1	NPD	EN 15088:2005
Bendability	NPD	
Fatigue strength	NPD	
Dangerous substances IDT EN 573-3	NO	
Durability rating IDT EN 1999-1-1	NPD	

The performance of the product identified above is in conformity with the declared performance/s.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011,
under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Paweł Rutecki
Director of Development and Investment

Konin, 13 April 2021
Director of Development & Investment


.....
Paweł Rutecki